

AUSFLOW

Multistream

Towed Behind

	M90003BH	M120004BH*	M140003BH*	M150004BH*	M180004BH*	M195005BH*
Total Tank Capacity (Lt)	9000	12000	13800	15300	18200	19700
Front Tank Capacity (Lt)	3000	3000	4700	4700	4700	4700
Second Tank Capacity (Lt)	3000	3000	4400	1500	4400	4400
Third Tank Capacity (Lt)	3000	3000	4700	4400	4400	1500
Fourth Tank Capacity (Lt)	N/A	3000	N/A	4700	4700	4400
Fifth Tank Capacity (Lt)	N/A	N/A	N/A	N/A	N/A	4700
Sixth Tank Capacity (Lt)	N/A	N/A	N/A	N/A	N/A	N/A
Seventh Tank Capacity (Lt)	N/A	N/A	N/A	N/A	N/A	N/A
Front Axle	Dolly	Steerer	Steerer	Steerer	Steerer	Steerer
Front Tyres	14.9x28	24.5x32	24.5x35	24.5x35	30.5x32	30.5x32
Rear Tyres	24.5x32	24.5x32	30.5x32	30.5x32	30.5x32	30.5x32
Drawbar Weight - empty (Kg)**	N/A	N/A	N/A	N/A	N/A	N/A
Drawbar Weight - full (Kg)**	N/A	N/A	N/A	N/A	N/A	N/A
Length (mm)	9800	11500	10300	10900	12100	12700
Width (mm)	3300	3300	3500	3500	3500	3500
Height (mm)	3400	3400	3800	3800	3800	3800
Auger	8"	8"	10"	10"	10"	10"
Engine Option Available	N/A	N/A	N/A	N/A	N/A	N/A

Notes for Multistreams

- All Machines include augers, hydraulic oil heat exchangers and full flow hydraulic filter with service indicator
- Variable rate standard on all models
- 3 metre track option available on (TBH) Tow Behind models
- Staggered axle option available on (TBH) Tow Behind models
- Choice of Topcon Eagle and X20 or Cambut controller suitable for Trimble FM 1000 monitor upto 4 tanks
- All tanks can be fitted with optional liquid delivery systems
- Specifications and dimensions are nominal and subject to change without notice or obligation
- Quoted tank volumes are nominal and subject to manufacturing tolerances
- *Towed behind Multistreams are not suitable for DBS Auseeders D260-70 and 'W' series
- Quoted weights are approximate and subject to product densities and % bin fill
- Quoted weights includes, small seed (SG 0.7), seed (SG 0.8), fertiliser (SG 1.0) and 1 x liquid on Multistream's (SG 1.32)
- **With engine option add 400Kg to the drawbar weights